NAME

recno – record number database access method

SYNOPSIS

#include <sys/types.h>
#include <db.h>

DESCRIPTION

The routine *dbopen* is the library interface to database files. One of the supported file formats is record number files. The general description of the database access methods is in *dbopen*(3), this manual page describes only the recno specific information.

The record number data structure is either variable or fixed-length records stored in a flat-file format, accessed by the logical record number. The existence of record number five implies the existence of records one through four, and the deletion of record number one causes record number five to be renumbered to record number four, as well as the cursor, if positioned after record number one, to shift down one record.

The recno access method specific data structure provided to *dbopen* is defined in the <db.h> include file as follows:

```
typedef struct {
        u_char bval;
        u_int cachesize;
        index_t psize;
        u_long flags;
        int lorder;
        size_t reclen;
        char *bfname;
} RECNOINFO;
```

The elements of this structure are defined as follows:

bval The delimiting byte to be used to mark the end of a record for variable-length records, and the pad character for fixed-length records. If no value is specified, newlines (''\n'') are used to mark the end of variable-length records and fixed-length records are padded with spaces.

cachesize
A suggested maximum size, in bytes, of the memory cache. This value is **only** advisory, and the access method will allocate more memory rather than fail. If *cachesize* is 0 (no size is specified) a default cache is used.

psize The recno access method stores the in-memory copies of its records in a btree. This value is the size (in bytes) of the pages used for nodes in that tree. If *psize* is 0 (no page size is specified) a page size is chosen based on the underlying file system I/O block size. See *btree*(3) for more information.

bfname The recno access method stores the in-memory copies of its records in a btree. If bfname is non-NULL, it specifies the name of the btree file, as if specified as the file name for a dbopen of a btree file.

flags The flag value is specified by *or*'ing any of the following values:

R_FIXEDLEN
The records are fixed-length, not byte delimited. The structure element *reclen* specifies the length of the record, and the structure element *bval* is used as the pad character.

R_NOKEY
In the interface specified by *dbopen*, the sequential record retrieval fills in both the caller's key and data structures. If the R_NOKEY flag is specified, the *cursor* routines are not required to fill in the key structure. This permits applications to retrieve records at the end of files without reading all of the intervening records.

R_SNAPSHOT
This flag requires that a snapshot of the file be taken when *dbopen* is called, instead of permitting any unmodified records to be read from the original file.

lorder The byte order for integers in the stored database metadata. The number should represent the order as an integer; for example, big endian order would be the number 4,321. If *lorder* is 0 (no order is specified) the current host order is used.

reclen The length of a fixed-length record.

The data part of the key/data pair used by the recno access method is the same as other access methods. The key is different. The *data* field of the key should be a pointer to a memory location of type *recno_t*, as defined in the <db.h> include file. This type is normally the largest unsigned integral type available to the implementation. The *size* field of the key should be the size of that type.

In the interface specified by *dbopen*, using the *put* interface to create a new record will cause the creation of multiple, empty records if the record number is more than one greater than the largest record currently in the database.

SEE ALSO

dbopen(3), *hash*(3), *mpool*(3), *recno*(3)

Document Processing in a Relational Database System, Michael Stonebraker, Heidi Stettner, Joseph Kalash, Antonin Guttman, Nadene Lynn, Memorandum No. UCB/ERL M82/32, May 1982.

BUGS

Only big and little endian byte order is supported.